

In the Claims:

1. (Currently Amended) A method for removing undesired occurrences in hair and fur, comprising the steps of using providing a mouthpiece with a mouth, the mouthpiece being connected to a source of vacuum through a tube and containing a filter and at least one comb wherein the mouthpiece has a longitudinal, inclining mouth, wherein the comb is fastened to a wall surrounding a first portion of ~~the~~ a front end of the mouth and ~~has a steep~~ is oriented at a transverse angle relative to the longitudinal axis of the mouthpiece, the comb covering a first, minor part of the mouth of the mouthpiece, wherein the mouth of the mouthpiece has an inclining wall surrounding a second, open part of the mouth, the inclining wall being at a first acute angle with respect to the longitudinal axis of the mouthpiece and being at a second obtuse angle with respect to the wall to which the comb is fastened; ~~and wherein sucking~~ sucking a sheaf of hair ~~is sucked~~ into the mouth whereby the sheaf of hair is hanging extended in the mouthpiece; tilting ~~wherein the comb is tilted~~ in over the sheaf of hair with an edge of points of teeth of the comb [is] in contact with scalp or skin on which the hair is growing; ~~wherein combing~~ combing the sheaf of hair ~~is combed~~ by pulling the comb through the sheaf of hair with the edge of the teeth in contact with the scalp or skin, ~~after which~~ and tilting the comb ~~is tilted~~ out of the sheaf of hair, wherein the ~~process including the~~ above steps is are repeated for the sheaf of hair causing undesired occurrences to be detached and sucked through the mouthpiece in order subsequently to be caught by the filter in the mouthpiece.

2. (Currently Amended) A The method according to claim 1, wherein the steps are repeated for different sheaves of hair.

3. (Currently Amended) A The method according to claim 1, wherein the comb is tilted freely in and out of the said sheaf simultaneously with combing with short strokes, wherein the edge of points of teeth in each combing movement is drawn over the scalp through the habitat area of ~~the~~ lice and vermin, and wherein the same area of the scalp is combed ~~with~~ at short intervals.

4. (Currently Amended) ~~An~~ A device for removing undesired occurrences in hair and fur, ~~where the device includes~~ comprising a mouthpiece ~~adapted to engage~~ engaged to one end of a tube attached to a source of vacuum, the mouthpiece including a mouth and at least one comb attached thereto, wherein the mouthpiece has a substantially elongated shape, wherein the mouth of the mouthpiece is arranged longitudinally inclining, forming an inclined first angle relative to the longitudinal axis of the mouthpiece, wherein the mouth of the mouthpiece has an inclining wall surrounding an open part of the mouth, the inclining wall being at said first angle with respect to the longitudinal axis of the mouthpiece and being at a second angle with respect to a wall to which the comb is attached; wherein the comb is arranged to form a second substantially orthogonal angle relative to the longitudinal axis of the mouthpiece, and wherein the comb covers less than half of the mouth of the mouthpiece.

5. (Currently Amended) The ~~An~~ device according to claim 4, wherein the device includes a filter with the shape of a cone and in the edge of which there is provided a number of slits wherein the filter is disposed in the mouth of the tube connecting to the source of vacuum, so that the edge of the filter in the length of the slits ~~are~~ is turned about the edge of the ~~vacuum-connecting tube~~ attached to the source of vacuum, and wherein it is retained by the connecting tube of the mouthpiece when the former is put on, and so that the said filter is easily detached from the point ~~as this~~ where it is visible in the connecting tube of the mouthpiece when the connecting tubes are separated.

6. (Currently Amended) The ~~An~~ device according to claim 4, wherein the comb is arranged uppermost in the mouth of the mouthpiece and is readily detachable, the comb covering a relatively small area of the total area of the mouth, so that the mouthpiece under the comb presents a relatively large and open mouth.

7. (Currently Amended) The ~~A~~ device according claim 4, wherein the mouth is substantially circular as seen from the front, and wherein the comb fixedly fits ~~tightly~~ to the adjacent edge of the mouth and extends in a plane substantially perpendicular to the longitudinal axis of the device.

8. (Currently Amended) The A device according to claim 4, wherein the comb presents an edge of points of teeth, and wherein the mouth inclines rearwards and downwards from the edge of points of teeth when the longitudinal axis of the mouthpiece extends substantially in horizontal direction.

9. (Currently Amended) The A device according to claim 4, wherein the mouthpiece has a rounded bulge at both sides of the comb, ~~forming that allows the comb to be tilted about~~ a tilt axis and simultaneously forming a combing support.

10. (Currently Amended) The A device according to claim 4, wherein a filter is provided in association with the device and is attached readily detachable, where the filter is shaped as a cone with slits along the edge.

11. (Currently Amended) The A device according to claim 10, wherein the device is provided with a further filter disposed upstream relative to the other filter, the further filter being readily detachable, shaped as a cone, and provided with a hole at the bottom.

12. (Currently Amended) The A device according to claim 4, wherein ~~the~~ a filter is captured ~~disposed~~ at a ~~transition joint~~ transition joint between a tube and a pipe, and wherein the ~~transition joint~~ joint is formed by a locking mechanism providing access to the filter after unlocking, that the filter is formed by a filter cylinder interacting with the internal wall of the pipe and containing a bottom formed by a filter.

13. (Currently Amended) The A device according to claim 12, ~~wherein the filter may further comprising be closed by a cover~~ that closes the filter when underpressure is present behind the filter, and wherein the cover includes an end piece and a cylinder, where the cylinder of the cover engages the internal wall of the filter cylinder.

14. (Currently Amended) The A device according to claim ~~13~~ 12, wherein the end piece is formed by a lens for watching the contents of the filter, and wherein the focus of the lens may be adjusted by more or less pressing the cylinder of the cover.

15. (Currently Amended) The A device according to claim 14 [12], wherein the lens is a Fresnel lens.

16. (Currently Amended) The A device according to claim 5 13, further comprising a cover that closes the filter when underpressure is present behind the filter, and wherein the cover includes an end piece and a cylinder, where the cylinder of the cover engages the internal wall of the filter cylinder, and wherein the end piece is formed by a lens for watching the contents of the filter, and wherein the focus of the lens may be adjusted by more or less pressing the cylinder of the cover.

17. (Currently Amended) The A device according to claim 16 [13], wherein the lens is a Fresnel lens.